

Factory Options

Region: North America
Market Segment: Winter Service
Specifications are subject to revision without prior notice.

Item	Description
Wheelbase	
154"	U500 model 405.230, 154", 3900 mm wheelbase
Tires	
4 x 395/85 R20	4 tires 395/85 R 20 Michelin XZL, 70 mph, 987-K57- 4/80 Snow chain use. Requires U82.
Paint	
MB9147, or MB9678	Arctic, or Pure White (to be determined)
Axles	
A52	Front axle differential lock
Brakes	
B42	Trailer air brake package
Chassis	
C47	Radiator protection
C88	Vertical exhaust pipe, right, chrome
Mounting and Fastening Parts	
D12	Front mounted implement plate.
D50	Rear mounting brackets.
Electrical System	
E44	Jump-start studs 12 Volt
E45	Front plug-in socket, 7 poles, SAEJ560
E53	Pre-wire mobile phone, 12V wiring and antenna.
E54	Pre-wire 2-way radio 12V including antenna only included with E37.
E55	Pre-wire AM/FM radio, antenna and 2 speakers.
Cabin	
F43	Webasto heating system, cab and engine coolant
Gearbox	
G21	Crawler and working gears. 16 additional forward and 16 additional reverse gears. 55.87:1
G48	EAS – Electro automatic shift system
Hydraulics	
H08	Dual circuit hydraulics with proportional valve.
H14	Hydraulic system, 4 valves.
H43	Tilting cylinder for tipper body.
H57	Hydraulic connection rear, 4 lines at valves 2, 3
H58	Pressure line rear for dual circuit hydraulics
H59	Separate hydraulic return line, rear
H61	Snow plow relief feature, weight transfer
H68	Additional hydraulic pressure line, behind cab, right
H75	Hydraulic connection front, 4 lines at valves 1, 2
H76	Hydraulic connection front, 4 lines at valves 3, 4
H78	Pressure line front for dual circuit hydraulics
H79	Separate hydraulic return line, front

Instruments, Signaling Equipment	
J48	Warning light for tilting cylinder.
Lights	
L07	Daytime running lights, mandatory for Canada
L47	Additional raised headlights for front-mounted implements, with raised additional indicator light
L58	Support for rotating beacon, road side
Engine	
M54	Block heater, electrical wiring and cable
M55	Fuel pre-warmer and water separator
M89	Grid heater at air intake.
PTO	
N08	Front PTO.
Platform	
P01	Quick release system for tipper cylinder.
P40	Platform tipper bed, side and rear panels removable to create flat bed, 11.3' x 7.3' x 15.8", forward wall 19.7"
P60	Sub-frame with ball points for body installation.
P82	Set of 4 tipping wells and bolts.
Trailer Couplings	
Q20	Tow hitch, Premier 240. 45'000 lb trailer weight.
Original Wheel Equipment	
R32	Rims 10.00V-20 for 395/85R20 tubeless, track 71.97" (1828 mm), not compatible with R41, R61.
Cab Equipment	
S02	Contoured air-suspended passenger seat, includes safety belt and head rest.
S12	Twin passenger seat.
S39	Power windows.
S82	Convex mirror, right side.
S86	Convex mirror, left side.
Additional Wheels	
T34	Spare rim and tire.
Speed Control	
V97	70 mph Speed limiter, for R32 tires
Parameter Settings	
Miscellaneous	
X18	GVW 33,000 lbs. Front axle 15,900 lbs, rear axle 18,700 lbs. Requires R32 and V97 for 70 mph.
Accessories	
Y76	License plate holder, front.
Compound Codes	
Z43	Parts for low temperature starting ability.
Additional Notes	
Winch	Front mounted 15,000 lb hydraulic Warn winch.
Mileage	Less than 7,200 miles.
Note	Tipper bed has some mounting holes for tank, etc.
End	