

Factory Options

Region: North America
Market Segment: Winter Service

Item	Description
Wheelbase	
154" (*see notes)	U500 model 405.230, 154", 3900 mm wheelbase
Tires	
4 x 395/85 R20	4 tires 395/85 R 20 Michelin XZL, 70 mph, 987-K57- 4/80 Snow chain use. Requires U82.
Paint	
MB9147, or MB9678	Arctic, or Pure White (to be determined)
Axles	
A30, A31	CTIS, Central tire inflation system
A52	Front axle differential lock
Brakes	
B42	Trailer air brake package
Chassis	
C47	Radiator protection
C50	VarioPilot, dual mode - left/right hand steering, no tray below breast possible, only with S86
C88	Vertical exhaust pipe, right, chrome
Mounting and Fastening Parts	
D12	Front implement mounting plate
D50	Rear mounting brackets.
Electrical System	
E44	Jump-start studs 12 Volt
E45	Front plug-in socket, 7 poles, SAEJ560
E53	Pre-wire mobile phone, 12V wiring and antenna.
E54	Pre-wire 2-way radio 12V including antenna only included with E37.
E55	Pre-wire AM/FM radio, antenna and 2 speakers.
Cabin	
F43	Webasto heating system, cab and engine coolant
Gearbox	
G21	Crawler and working gears. 16 additional forward and 16 additional reverse gears. 55.87:1
G48	EAS – Electro automatic shift system
Hydraulics	
H08 Package includes	Dual circuit hydraulic system with proportional valves. 2 valves, 4 lines, front and rear. Oil cooler.
H06, H12, H13, H14	Hydraulics, rear 4 valves
H57	Pressure line, rear, dual circuit hydraulics
H59	Snow plow weight transfer control
H61	Hydraulic line behind cab, and front left
H68, H78	Hydraulics lines, front left and right, 4 lines
H75, H76	Hydraulic return line, front
H79	Flush face couplers (standard)
H85	

Instruments, Signaling Equipment	
J48	Warning light for tilting cylinder, disconnected.
Lights	
L07	Daytime running light, mandatory for Canada
L58	Support for rotating beacon, right side.
Engine	
M54	Block heater, electrical wiring and cable
M55	Fuel pre-warmer and water separator
M89	Grid heater at air intake.
PTO	
N05	Rear engine live PTO to drive fluid pumps.
N08	Front PTO.
Platform	
	See notes
Trailer Couplings	
Q20	Tow hitch, Premier 240. 45'000 lb trailer weight.
Original Wheel Equipment	
R34	Rims 10.00V-20 for 395/85R20 tubeless, track 71.97" (1828 mm), not compatible with R41, R61.
Cab Equipment	
S02	Contoured air-suspended passenger seat, includes safety belt and head rest.
S10	Contoured air-suspended passenger seat, includes safety belt and head rest.
S26	Heatable windshield.
S39	Power windows.
S82	Convex mirror, right side.
S83	Down view mirrors, both left and right side.
S86	Wide angle convex rear mirror, right side.
Additional Wheels	
Speed Control	
V97	70 mph Speed limiter, for R34 tires
Parameter Settings	
Miscellaneous	
X18	GVW 33,000 lbs. Front axle 15,900 lbs, rear axle 18,700 lbs. Requires R34 and V97 for 70 mph maximum speed.
Accessories	
Y31	Tire inflation hose with pressure gauge, includes compressed air connection on outside.
Y76	License plate holder, front.
Compound Codes	
Additional Notes	
Wheelbase	190" wheelbase, chassis extended 36"
Platform	Custom subframe bolted to chassis, 72" x120" long
Winch	Rear mounted winch.
Mileage	Less than 8,000 miles.
End	