

Factory Options

| | |
|---|--|
| Region: | North America |
| Market Segment: | Winter Service |
| Vehicle Number: | 202481 |
| Item | Description |
| 154" Wheelbase | U500 NA model 405.230, 154", 3900 mm wheelbase |
| Tires | |
| 4 x 395/85 R20 | 4 tubeless tires 395/85 R20 Michelin XZL, 70 mph, 987-K57- 4/80 Snow chain use. Requires U82. |
| Paint | |
| MB9147, or MB9678 | Arctic, or Pure White (to be determined) |
| Axles | |
| A30, A31 | Central Tire Inflation System (CTIS) |
| A52 | Front axle differential lock |
| Brakes | |
| B42 | Trailer air brake package |
| Chassis | |
| C47 | Radiator protection |
| C50 | VarioPilot, dual mode - left/right hand steering, no tray below breast possible, only with S86 |
| C88 | Vertical exhaust pipe, right, chrome |
| Mounting and Fastening Parts | |
| D50 | Rear mounting brackets. |
| Electrical System | |
| E44 | Jump-start studs 12 Volt |
| E45 | Front plug-in socket, 7 poles, SAEJ560 |
| E47 | |
| E53 | Pre-wire mobile phone, 12V wiring and antenna. |
| E54 | Pre-wire 2-way radio 12V including antenna only included with E37. |
| E55 | Pre-wire AM/FM radio, antenna and 2 speakers. |
| Cabin | |
| F43 | Webasto heating system, cab and engine coolant. |
| Gearbox | |
| G21 | Crawler and working gears. 16 additional forward and 16 additional reverse gears (24 gears total). 55.87:1 |
| Hydraulics | |
| H08 Package includes | Dual circuit hydraulic system with proportional valves. 2 valves, 4 lines, front and rear. Oil cooler. |
| H14, H57, H58, H59, H61, H68, H75, H76, H78, H79 | |
| H43 | Tilting cylinder for tipper body. |
| Instruments, Signaling Equipment | |
| J48 | Warning light for tilting cylinder. |
| Lights | |
| L47 | Additional raised headlights and indicator lights for front-mounted implements. |
| L59 | Support for rotating beacon, road and curb side. |

| | |
|---------------------------------|---|
| Engine | |
| M03 | Increased engine output power, 280 hp, 800 ft-lbs. |
| M37 | High Output Alternator, 270 amps |
| M54 | Engine Block Heater, electrical wiring and cable |
| M55 | Fuel pre-warmer and fuel-water separator. |
| M89 | Grid heater at air intake. |
| PTO | |
| N08 | Live PTO, incl. PTO front. |
| N18 | Retro-fitting possibilities for gearbox PTO. |
| Platform | |
| P01* | Quick release system for tipper cylinder. |
| P40 | Platform tipper bed, side and rear panels removable to create flat bed, 11.3 x 7.3 x 15.8 ft, forward wall 19.7 in |
| P60 * | Sub-frame with ball points for body installation. |
| P82 * | Set of 4 tipping wells and bolts. |
| Tow Hitch | |
| Q20 | Tow Hitch, Premiere 240; 45,000 lb trailer, 6,000 lb tongue. |
| Original Wheel Equipment | |
| R34* | Rims 10.00V-20 for 395/85 R20 tubeless tires, track 71.97" (1828 mm), includes rear mud guards, CTIS possible. |
| Cab Equipment | |
| S02 | Contoured air-suspended passenger seat, includes safety belt and head rest. |
| S10 | Contoured air-suspended passenger seat, includes safety belt and head rest. |
| S26 | Heatable windshield. |
| S39 | Power windows. |
| S49 | Sliding Rear Window. |
| S82 | Convex mirror, right side. |
| S83 | Down view mirrors, both left and right side. |
| S86 | Wide angle convex rear mirror, right side. |
| Additional Wheels | |
| T34 * | Spare Rim 10.00V-20 with 395/85 R20 tubeless tire. |
| Speed Control | |
| V97 | 70 mph Speed limiter, for R34 tires |
| Miscellaneous | |
| X18 Retrofitted | GVW 33,000 lbs. Front axle 15,900 lbs, rear axle 18,700 lbs. Requires R34 and V97 for 70 mph maximum speed. |
| Accessories | |
| Y31 | Tire inflation hose, pressure gauge, includes compressed air connection on outside. |
| Compound Codes | |
| Z43 | Low temp cold start. Low temp steering oil, antifreeze |
| Z68 | Sea conservation. |
| Z99 | Text order. |
| Additional Notes | |
| Information Notice | Information provided on these web pages and documents is deemed reliable but is not guaranteed, it may contain errors and omissions, and is subject to change without prior notice. |
| Recalls | All recalls are up to date. |
| Mileage | 14,320 miles. |
| Updated 06/30/2014 | Verify items marked *. |
| END | |

