

## Factory Options

<b>Region:</b>	<b>North America</b>
<b>Market Segment:</b>	<b>Winter Service</b>
<b>Item</b>	<b>Description</b>
<b>Wheelbase</b>	
154"	U500 model 405.230, 154", 3900 mm wheelbase
<b>Tires</b>	
4 x 395/85 R20	4 tires 395/85 R 20 Michelin XZL, 70 mph, 987-K57- 4/80 Snow chain use. Requires U82.
<b>Paint</b>	
MB9147, or MB9678	Arctic, or Pure White (to be determined)
<b>Axles</b>	
A52	Front axle differential lock
<b>Brakes</b>	
B42	Trailer air brake package
<b>Chassis</b>	
C47	Radiator protection
C50	VarioPilot, dual mode - left/right hand steering, no tray below breast possible, only with S86
C88	Vertical exhaust pipe, right, chrome
<b>Mounting and Fastening Parts</b>	
D12	<b><i>No Implement Mounting Plate included due to installation of winch. Plate available from third-party for \$500 plus shipping.</i></b>
D50	Integrated Implement Support is included. Rear mounting brackets.
<b>Electrical System</b>	
E44	Jump-start studs 12 Volt
E45	Front plug-in socket, 7 poles, SAEJ560
E53	Pre-wire mobile phone, 12V wiring and antenna.
E54	Pre-wire 2-way radio 12V including antenna only included with E37.
E55	Pre-wire AM/FM radio, antenna and 2 speakers. <b><i>Alpine receiver with CD player and speakers</i></b>
<b>Cabin</b>	
F43	Webasto heating system, cab and engine coolant
<b>Gearbox</b>	
G21	Crawler and working gears. 16 additional forward and 16 additional reverse gears. 55.87:1
G48	EAS – Electro automatic shift system
<b>Hydraulics</b>	
H08 Package includes H06, H12, H13, H14 H43	Dual circuit hydraulic system with proportional valves. 2 valves, 4 lines, front and rear. Oil cooler. Tilting cylinder for tipper body.
<b>Instruments, Signaling Equipment</b>	
J48	Warning light for tilting cylinder.
<b>Lights</b>	
L07	Daytime running light, mandatory for Canada
L47	Additional raised headlights for front-mounted implements, with raised additional indicator light.

L59

Support for rotating beacon, road and curb side.

<b>Engine</b>	
M54	Block heater, electrical wiring and cable
M55	Fuel pre-warmer and water separator
M89	Grid heater at air intake.
<b>PTO</b>	
N05	Rear engine live PTO to drive fluid pumps.
<b>Platform</b>	
P01	Quick release system for tipper cylinder.
P40	Platform tipper bed, side and rear panels removable to create flat bed, 11.3' x 7.3' x 15.8", forward wall 19.7"
P60	Sub-frame with ball points for body installation.
P82	Set of 4 tipping wells and bolts.
<b>Trailer Couplings</b>	
Q20	Tow hitch, Premier 240. 45'000 lb trailer weight.
<b>Original Wheel Equipment</b>	
R34	Rims 10.00V-20 for 395/85R20 tubeless, track 71.97" (1828 mm), not compatible with R41, R61.
<b>Cab Equipment</b>	
S02	Contoured air-suspended passenger seat, includes safety belt and head rest.
S10	Contoured air-suspended passenger seat, includes safety belt and head rest.
S26	Heatable windshield.
S39	Power windows.
S82	Convex mirror, right side.
S83	Down view mirrors, both left and right side.
S86	Wide angle convex rear mirror, right side.
<b>Additional Wheels</b>	
<b>Speed Control</b>	
V97	70 mph Speed limiter, for R34 tires
<b>Parameter Settings</b>	
<b>Miscellaneous</b>	
X18	GVW 33,000 lbs. Front axle 15,900 lbs, rear axle 18,700 lbs. Requires R34 and V97 for 70 mph maximum speed.
<b>Accessories</b>	
Y31	Tire inflation hose with pressure gauge, includes compressed air connection on outside.
<b>Compound Codes</b>	
<b>Additional Notes</b>	
Winch	Front mounted 15,000 lb hydraulic NHW winch.
Mileage	Less than 5,050 miles.
Recalls	All recalls are up to date.
<b>End</b>	

**Note** - Information provided on these web pages and documents is deemed reliable but is not guaranteed, it may contain errors and omissions, and is subject to change without prior notice.

Updated 9/20/2013