

Factory Options	
Region:	North America
Market Segment:	Winter Service
Item	Description
Wheelbase	
154"	U500 model 405.210, 132", 3350 mm wheelbase
Tires	
4 x 395/85 R20	4 tires 395/85 R 20 Michelin XZL, 70 mph, 987-K57- 80, no snow chains.
Paint	
MB5318	Ultramarine Blue
Axles	
A30	Central Tire Inflation Systems (CTIS)
A31	Necessary parts for CTIS A30+(R32/R34/R61)
A52	Front axle differential lock
Brakes	
B42	Trailer air brake package
Chassis	
C88	Vertical exhaust pipe, right, chrome
Mounting and Fastening Parts	
D12	Front mounted implement plate.
Electrical System	
E44	Jump-start studs 12 Volt
E45	Front plug-in socket, 7 poles, SAEJ560
E53	Pre-wire mobile phone, 12V wiring and antenna.
E54	Pre-wire 2-way radio 12V including antenna only included with E37.
E55	Pre-wire AM/FM radio, antenna and 2 speakers.
Gearbox	
G21	Crawler and working gears. 16 additional forward and 16 additional reverse gears. 55.87:1
G48	EAS – Electro automatic shift system
Hydraulics	
H06	Dual circuit hydraulic system.
H13	Hydraulic system, 3 valves.
H43	Tilting cylinder for tipper body.
H57	Hydraulic connection rear, 4 lines at valves 2, 3
H58	Pressure line rear for dual circuit hydraulics
H59	Separate hydraulic return line, rear
H73	Hydraulic connection front, 2 lines at valves 3 only
H75	Hydraulic connection front, 4 lines at valves 1, 2
H78	Pressure line front for dual circuit hydraulics
H79	Separate hydraulic return line, front
Instruments, Signaling Equipment	
J48	Warning light for tilting cylinder.
Lights	
L07	Daytime running lights, mandatory for Canada
L47	Additional raised headlights for front-mounted implements, with raised additional indicator light

L58	Support for rotating beacon, road side
Engine	
M55	Fuel pre-warmer and water separator
M89	Grid heater at air intake.
PTO	
N05	Live engine PTO.
N08	Live front PTO, 1'000 rpm, with cooling and driveshaft 1-3/4" spline.
Platform	
P01	Quick release system for tipper cylinder.
P27	Platform tipper bed, side and rear panels removable to create flat bed, 8.75' x 7.21' x 15.8", forward wall 19.7"
P60	Sub-frame with ball points for body installation.
P82	Set of 4 tipping wells and bolts.
Original Wheel Equipment	
R34 with CTIS	Rims 10.00V-20 for 395/85R20 tubeless, track 71.97" (1828 mm), with rear mud guards, no use of snow chains.
Cab Equipment	
S02	Contoured air-suspended passenger seat, includes safety belt and head rest.
S39	Power windows.
S82	Convex mirror, right side.
S86	Convex mirror, left side.
Additional Wheels	
	None
Speed Control	
V97	70 mph Speed limiter, for R32 tires
Parameter Settings	
Miscellaneous	
X18	GVW 33,000 lbs. Front axle 15,900 lbs, rear axle 18,700 lbs. Requires R34 and V97 for 70 mph.
Additional Notes	
Winch	Front mounted hydraulic winch.
Winch	Rear mounted 15,000 lb hydraulic Warn winch. Custom mounting plate, high and low 2" receivers.
Mileage	Less than 42,500 miles.
Note	All recalls are up to date.
End	

Note - Information provided on these web pages and documents is deemed reliable but is not guaranteed, it may contain errors and omissions, and is subject to change without prior notice.
Updated 4/30/2015